

Operation Manual

Alarming cell phone display stand(A32)

Alarm display stand specification:

Applicable products: cell phone, MP3, MP4, razors and other digital products

Material:ABS and Aluminum Alloy with anodized

Produce technics: Sandblasting and Oxidizing

color: Silvery white,Black,or customized

Size: L95*W72*H163MM

Weight:0.3KG

Bearing weight: 10KGS

Input voltage: 110V-240V(50-60HZ)

Output voltage:5V/2A

Battery: internal lithium battery 480MA

Standby time: 3-6 months

Alarm volume: 90-110 DB within 80cm

Alarm condition: Low voltage 3.4V/charging sensor cable is disconnected

Remote controller: infrared decoding within 2 M

Working environment: (-10℃~50℃) RF≤95%

Product features

- 1.Applied to universal cell phone security alarm with charging function
- 2.The PCB with over current protection function,the device will more durable
- 3.The surface is sand blasted and oxidized, more smooth,high quality



- 4.Smart sensor touch, more security
- 5.Display Angle of 60 degrees,perfect show
- 6.Infrared decoder can be control within 1-2m space
- 7.Flexible spiral recoil sensor cable

Operation steps



1.Tear off base bottom protective film.



2.To paste on a clear and flat display stand.



3.Put RJ11 port into hole alarm holder.



4.Tear off the touch sensor protective film.



5.To paste the display product onto the touch sensor.



6.Insert the charge cable into DC hole.



7.Insert the Micro USB into mobile phone.



8.Insert the power line into the left USB of the Alarm.



9.Connected with Micro USB port the alarm holder will work start charge



10.Original Password is 345.Use remote controller forward and alarm press 3.4.5 which can unlock the alarm sounds.

Method of use:

- 1) Remove the adhesive protective film at the bottom of the alarm device and fixed it on the clean and flat table
- 2) Remove the adhesive protective film at the the sensor and put the digital products on it,if the alarm ring one second, show that alarm running normally
- 3) Connect the power cable on the left of alarm device,the red light on means the charging is start ,if the power full it will automatically shut down
- 4) If the Blue light on means the alarm did not enter the working state or alarm device broken
- 5) The factory code is 3, 4, 5.If there is any alarm, please press 3, 4, 5 consecutive key can cancel the alarm sound

The usage methods of remote control

- 1) Change password: from the alarm telephone jack pulled out induction on the right side of the spring line alarm will report to the police. At this time Blue light is flashing
2. Press the password remove alarm then long press the set button for five seconds after hearing 1 ring enter the old password,if insert is correct the alarm will got two seconds long rang ,then put in the new password and then enter three digits long alarm ring at this time for 2 seconds, and then enter the new password again after two new password input is correct ,the alarm will ring 3 sounds means the password was changed success
3. Note: the password for the 3 digits,the new password input must be the same input two intervals of not more than 15 seconds

more than 15 seconds alarm will ring a loud said to modify the password timeout needs according to modify the Setting button of the remote control again

4.Forgot password: remove the alarm from the desktop ,using the paper clip insert at this side of alarm holes and blue light is flashing 3 times means the alarm restore factory state, 3, 4, 5 is the password of the factory status,.

Attention

1. Forbid dismantle any part of the product
2. The built-in battery standby for six months, if the battery power is insufficient, please recharge in time
3. To ensure that the host for normal inspection of each communication port to connect each sensor communication line all keep right
4. To prolong battery life, it is recommended that the exhibition machine normal charging time not more than eight hours,no need to charging long time
5. if the viscose not in-stable, please don't continue to use it for your product safety

Packaging Details

Package List:1pc security stand+1pc power adapter +1Cable sensor +1Key/inner box/ 26inner boxes / CTN

Package Weight:8.6kg

Package Size:44cm x 29cm x 35cm (17.32" x 11.42" x 13.78")

Tips:Typically 5pcs Free product with a digital code to unlock, which can be based on the actual situation!